





This is to certify that:

RPB Safety LLC 2807 Samoset Rd Royal Oak Michigan 48073 USA

Holds Certificate Number:

CE 718714

In respect of:

PX5 PAPR System to EN 12941:2023;

Incorporating the following headtop systems:

T-Link, Z-Link Respiratory Helmet with Full Face Visor & optional ear-muff protector to EN 166:2001, EN 812:2012 & EN 352-3:2020;

Z4 Welding Helmet to EN 166:2001, EN 175:1997, EN 379:2003+A1:2009, EN 812:2012 & EN 352-1:2020

T200 Headtop to EN 166:2001 & EN 352-1:2020

on the basis that BSI carried out the relevant Type Examination procedures under the requirements with the Regulation (EU) 2016/425 of the European Parliament and Council relating to Personal Protective Equipment Regulation (PPE) Annex V (Module B) and meets the relevant health and safety requirements specified in Annex II

For and on behalf of BSI, a Notified Body for the above Regulation (Notified Body Number 2797):

Graeme Tunbridge, Senior Vice President Global Regulatory & Quality

First Issued: 2020-06-02 Latest Issue: 2025-07-08 Effective Date: 2025-07-08 Expiry Date: 2030-06-02

Page: 1 of 11



This certificate has been issued by and remains the property of BSI Group The Netherlands B.V., John M. Keynesplein 9, 1066 EP Amsterdam, The Netherlands and should be returned immediately upon request.

No. CE 718714

**Product Specification** 

Range: PX5 Advanced PAPR System incorporating the following Head-tops:

**Head-tops:** T-LINK, Z-LINK, Z4, & T200.

**Technical Specification:** EN 12941:2023 – Respiratory protective devices. Powered filtering devices

incorporating a loose fitting respiratory interface. Requirements, testing, marking.

**Product Description:** The RPB® PX5® is approved as a Powered Air Purifying Respirator Fan Unit to EN

12941:2023, designed to be used in conjunction with the approved RPB® head-tops

for different applications where there is a need for protection from airborne

contaminants such as welding, grinding, painting, and other construction and industrial applications, depending on the selected head-top. For applications such as welding or grinding that produce sparks or high heat, a FR (Fire Retardant) specific model is

available, with a FR belt and spark arrester to prevent

sparks from entering the PAPR and igniting the filter material.

For applications that need cleaning and disinfecting, a DC (Easy Clean) specific model

is available, with a DC Belt which has a coating for easily wiping and washing.

**Model numbers:** 03-801, 03-801-FR, 03-801-DC (HEPA Filter Configurations)

03-802, 03-802-FR, 03-802-DC (Combination Filter Configurations) 03-803-FR, 03-803-DC (HEPA Filter Configurations with Back-Pack)

03-804-FR, 03-804-DC (Combination Filter Configurations with Back-Pack)

Page: 2 of 11

This certificate has been issued by and remains the property of BSI Group The Netherlands B.V., John M. Keynesplein 9, 1066 EP Amsterdam, The Netherlands and should be returned immediately upon request.

No. CE 718714

|          |              |                  |          | Filters Options        |                        |                               | Filters Options                    |                                  |                          |                       | Filters Options Hose |                             |                         |                       | Belt/Backpack Batter                    |                                       |                                       |  | tery                     | Cape/Face Seal/Chin Seal     |                              |                                  |                                       | Hoods                                     |                                   |                              |                           |                           |   | Radiant Heat              |                           |                                    |   |                        |  |  |                               |                                |  |
|----------|--------------|------------------|----------|------------------------|------------------------|-------------------------------|------------------------------------|----------------------------------|--------------------------|-----------------------|----------------------|-----------------------------|-------------------------|-----------------------|---|---------------------------------------|---------------------------------------|--|--------------------------|------------------------------|------------------------------|----------------------------------|---------------------------------------|---|-----------------------------------|------------------------------|---------------------------|---------------------------|---|---------------------------|---------------------------|------------------------------------|---|------------------------|--|--|-------------------------------|--------------------------------|--|
| Headtops | Standards    | Protection Level | MMDF     | Number of Filters Used | 03-892-P P R SL (HEPA) | 03-893-A2 A2P R SL (Combined) | 03-895-ABEK ABEK1P R SL (Combined) | 03-894-ABE ABE1P R SL (Combined) | 04-831 - Standard Length | 04-841 - Short Length | 07-765 - Nylon Belt  | 07-765-DC - Easy Clean Belt | 07-765-FR Nomex FR Belt | 03-811 - Belt Support | 03-822-DC - Easy Clean Backpack Harness | 03-822-FR - Nomex FR Backpack Harness | 03-855 - Standard Lithium Ion Battery | 03-856 - High Capacity Lithium Ion Battery | 15-711 - 24 FR Face Seal | 15-721 - 24 FR Shoulder Cape | 16-711 - Z-Link FR Face Seal | 16-721 - Z-Link FR Shoulder Cape | 16-712 - Z-Link Tychem 2000 Face Seal | 16-723 - Z-Link Tychem 4000 Shoulder Cape | 16-724 - Aluminized Shoulder Cape | 16-731 - Z-Link FR Chin Seal | 17-712 - Tychem 2000 Hood | 17-713 - Tychem 4000 Hood | 17-713-SX - Tychem 4000 Hood - Safety Lens, XL Cape | 17-722 - Tychem 2000 Hood | 17-732 - Tychem 2000 Hood | 16-675-GT - Radian Heat Gold Visor | 16-675-GTIR5 - Radian Heat Gold IR5 Visor | 16-675-IR5 - IR5 Visor | 16-675-HGT - Radian Heat Half Gold Visor | 16-675-GT3 - Radian Heat Gold Visor, Shade 3 | 16-744 - Aluminized Top Cover | 16-744 - Aluminized Rear Cover | 04-855 - Aluminized Breathing Tube Cover |
| Z4       | EN12941:2023 | TH2              | 170l/min | 1                      | Yes                    | Yes                           | Yes                                | Yes                              | Yes                      |                       | Yes                  | Yes                         | Yes                     | Yes                   |   |                                       | Yes                                   | Yes  | Yes                      | Yes                          |                              |                                  |                                       |   |                                   |                              |                           |                           |   |                           |                           |                                    |   |                        |  |  |                               |                                |  |
| Z4       | EN12941:2023 | TH2              | 170l/min | 1                      | Yes                    | Yes                           | Yes                                | Yes                              |                          | Yes                   |                      |                             |                         |                       | Yes                                     | Yes                                   | Yes                                   | Yes  | Yes                      | Yes                          |                              |                                  |                                       |   |                                   |                              |                           |                           |   |                           |                           |                                    |   |                        |  |  |                               |                                |  |
| Z-Link   | EN12941:2023 | TH3              | 170l/min | 1                      | Yes                    | Yes                           | Yes                                | Yes                              | Yes                      |                       | Yes                  | Yes                         | Yes                     | Yes                   |   |                                       | Yes                                   | Yes  |                          |                              |                              | Yes                              |                                       | Yes                                       | Yes                               |                              |                           |                           |   |                           |                           | Yes                                | Yes                                       | Yes                    | Yes                                      | Yes  | Yes                           | Yes                            | Yes                                      |
| Z-Link   | EN12941:2023 | TH3              | 170l/min | 1                      | Yes                    | Yes                           | Yes                                | Yes                              |                          | Yes                   |                      |                             |                         |                       | Yes                                     | Yes                                   | Yes                                   | Yes  |                          |                              |                              | Yes                              |                                       | Yes                                       | Yes                               |                              |                           |                           |   |                           |                           | Yes                                | Yes                                       | Yes                    | Yes                                      | Yes  | Yes                           | Yes                            | Yes                                      |
| Z-Link   | EN12941:2023 | TH2              | 170l/min | 1                      | Yes                    | Yes                           | Yes                                | Yes                              | Yes                      |                       | Yes                  | Yes                         | Yes                     | Yes                   |   |                                       | Yes                                   | Yes  |                          |                              | Yes                          |                                  | Yes                                   |   |                                   | Yes                          |                           |                           |   |                           |                           |                                    |   |                        |  |  |                               | $ldsymbol{\Box}$               |  |
| Z-Link   | EN12941:2023 | TH2              | 170l/min | 1                      | Yes                    | Yes                           | Yes                                | Yes                              |                          | Yes                   |                      |                             |                         |                       | Yes                                     | Yes                                   | Yes                                   | Yes  |                          |                              | Yes                          |                                  | Yes                                   |   |                                   | Yes                          |                           |                           |   |                           |                           |                                    |   |                        |  |  |                               |                                |  |
| T-Link   | EN12941:2023 | TH3              | 170l/min | 1                      | Yes                    | Yes                           | Yes                                | Yes                              | Yes                      |                       | Yes                  | Yes                         | Yes                     | Yes                   |   |                                       | Yes                                   | Yes  |                          |                              |                              |                                  |                                       |   |                                   |                              | Yes                       | Yes                       | Yes   |                           |                           |                                    |   |                        |  |  |                               |                                |  |
| T-Link   | EN12941:2023 | TH3              | 170l/min | 1                      | Yes                    | Yes                           | Yes                                | Yes                              |                          | Yes                   |                      |                             |                         |                       | Yes                                     | Yes                                   | Yes                                   | Yes  |                          |                              |                              |                                  |                                       |   |                                   |                              | Yes                       | Yes                       | Yes   |                           |                           |                                    |   |                        |  |  |                               |                                |  |
| T200     | EN12941:2023 | TH3              | 170l/min | 1                      | Yes                    | Yes                           | Yes                                | Yes                              | Yes                      |                       | Yes                  | Yes                         | Yes                     | Yes                   |   |                                       | Yes                                   | Yes  |                          |                              |                              |                                  |                                       |   |                                   |                              | Yes                       | Yes                       | Yes   | Yes                       | Yes                       |                                    |   |                        |  |  |                               |                                |  |
| T200     | EN12941:2023 | TH3              | 170l/min | 1                      | Yes                    | Yes                           | Yes                                | Yes                              |                          | Yes                   |                      |                             |                         |                       | Yes                                     | Yes                                   | Yes                                   | Yes  |                          | 7                            |                              |                                  |                                       |   |                                   | 7                            | Yes                       | Yes                       | Yes   | Yes                       | Yes                       |                                    |   |                        |  |  |                               |                                |  |

No. CE 718714

**Associated Head-Tops:** 

Product name: T-LINK PAPR Respiratory Helmet with Full Face Visor.

Product variants: Standard Bib - TH3

Extra Long Bib - TH3

**Product type:** T-Link Respiratory Helmet with Full Face Visor & optional Ear-muffs.

The T-Link Respiratory Helmet with Full Face Visor is designed to only be used as part

of RPB PX5 AIR Respiratory systems approved to EN 12941:2023.

The T-Link is designed to operate with a flow rate between 180-230 litres per minute and compatible for use with the PX5 PAPR system. Respiratory characteristics are

specified on page 2 of this certificate.

The T-Link Helmet is approved to be used in combination with the Quiet Link Ear-muffs to EN 352-3:2020 Hearing protectors — Ear-muffs attached to an Industrial Helmet.

**Technical Specification and Classifications:** 

EN 12941:2023 – Respiratory protective devices. Powered filtering devices incorporating a loose fitting respiratory interface. Requirements, testing, marking.

| FILTER   | MMDF      | MIN RUN TIME        |
|----------|-----------|---------------------|
| HEPA     | 170 l/min | 10.00 hrs (Speed 1) |
|          |           | 07.00 hrs (Speed 2) |
|          |           | 06.00 hrs (Speed 3) |
|          |           |                     |
| Combined | 170 l/min | 05.00 hrs (Speed 1) |
|          |           | 04.00 hrs (Speed 2) |
|          |           | 04.00 hrs (Speed 3) |

EN 166:2001 Personal eye-protection – Optical class 1, Impact Low and liquid splash.

Classification: 1 F 3

EN 812:2012 Industrial Bump Cap

The T-link Respiratory Helmet meets Technical Specification to the mechanical requirements of EN 397:2012+A1:2012, 5.1.1 Shock Absorption, 5.1.2 Resistance to

penetration & 5.1.3 Flame Resistance

Page: 4 of 11

This certificate has been issued by and remains the property of BSI Group The Netherlands B.V., John M. Keynesplein 9, 1066 EP Amsterdam, The Netherlands and should be returned immediately upon request.

No. CE 718714

# Technical Specification and Classifications<sup>cont'd</sup>:

#### **Quiet Link Ear-Muff (with T-link Respiratory Helmet with Full Face Visor)**

EN 352-3:2020 Hearing protectors – Ear-Muff attached to an Industrial Helmet.

 $SNR_m = 35.8$   $SNR_s = 1.9$ SNR(dB) = 34

Page: 5 of 11

This certificate has been issued by and remains the property of BSI Group The Netherlands B.V., John M. Keynesplein 9, 1066 EP Amsterdam, The Netherlands and should be returned immediately upon request.

should be returned immediately upon request. To check its validity telephone +31 20 3460780. An electronic certificate can be authenticated online.

No. CE 718714

Product name: Z-LINK PAPR Respiratory Helmet with Full Face Visor.

Product variants: Face Seal - TH2

Chin Seal - TH2 Shoulder Cape - TH3

**Product type:** Z-Link Respiratory Helmet with Full Face Visor & optional Ear-muffs.

The Z-Link Respiratory Helmet with Full Face Visor is designed to be used as part

of RPB PX5 AIR Respiratory systems approved to EN 12941:2023.

The Z-Link is designed to operate with a flow rate between 180-230 litres per minute and compatible for use with the PX5 PAPR systems. Respiratory characteristics

are specified on page 2 of this certificate.

The Z-Link Helmet is approved to be used in combination with the Quiet Link Ear-muffs to EN 352-3:2020 Hearing protectors – Ear-muffs attached to an Industrial Helmet.

**Technical Specification and Classifications:** 

EN 12941:2023 – Respiratory protective devices. Powered filtering devices incorporating a loose fitting respiratory interface. Requirements, testing, marking.

| <b>Filter</b><br>HEPA | <b>MMDF</b><br>170 l/min | Min Run Time<br>10.00 hrs (Speed 1) |
|-----------------------|--------------------------|-------------------------------------|
|                       |                          | 07.00 hrs (Speed 2)                 |
|                       |                          | 06.00 hrs (Speed 3)                 |
|                       |                          |                                     |
| Combined              | 170 l/min                | 05.00 hrs (Speed 1)                 |
|                       |                          | 04.00 hrs (Speed 2)                 |
|                       |                          | 04.00 hrs (Speed 3)                 |

EN 166:2001 Personal eye-protection – Optical class 1, Impact for high speed particles at extreme temperature. molten metal hot solids and liquid splash.

Classification: 1 BT 9 3

EN 169:2002, EN 170:2002 & EN 172:1994+A2:2001 filter requirements.

| Filter Type: | Scale:          |
|--------------|-----------------|
| Clear        | 2-1.2 or 2C-1.2 |
| Smoke        | 5-3.1           |
| Yellow       | 2-1.2 or 2C-1.2 |
| Mirror       | 5-3.1           |
| IR5          | 4-5             |

Page: 6 of 11

This certificate has been issued by and remains the property of BSI Group The Netherlands B.V., John M. Keynesplein 9, 1066 EP Amsterdam, The Netherlands and should be returned immediately upon request.

No. CE 718714

# Technical Specification and Classifications<sup>cont'd</sup>:

The Z-link Respiratory Helmet meets a Technical Specification to the mechanical requirements of EN 397:2012+A1:2012, 5.1.1 Shock Absorption, 5.1.2 Resistance to penetration & 5.1.3 Flame Resistance and very low temperature, Molten Metal Splash, Lateral Deformation and Electrical Properties (440v) only.

Classification: -30°C / 440 V a.c / LD / MM

#### Quiet Link Ear-Muff (with Z-link Respiratory Helmet with Full Face Visor)

EN 352-3:2020 Hearing protectors – Ear-Muff attached to an Industrial Helmet.

 $SNR_m = 33.7$   $SNR_s = 2.1$ SNR(dB) = 32

Page: 7 of 11

This certificate has been issued by and remains the property of BSI Group The Netherlands B.V., John M. Keynesplein 9, 1066 EP Amsterdam, The Netherlands and should be returned immediately upon request.

should be returned immediately upon request. To check its validity telephone +31 20 3460780. An electronic certificate can be authenticated online.

No. CE 718714

**Product name: Z4 PAPR Respiratory Helmet with Full Face Visor.** 

**Product variants:** Face Seal -TH<sub>2</sub>

Shoulder Cape - TH2

Z4 Welding Helmet with full face visor & optional earmuffs. The Helmet is designed to **Product type:** 

be fitted with ADF units approved to EN 379:2003+A1:2009 and meets the

requirements of EN 175:1997.

The Z4 Welding Helmet with full face visor is designed to only be used as part of RPB

PX5 AIR Respiratory systems approved to EN 12941:2023.

The Z4 is designed to operate with a flow rate between 180-230 litres per minute and compatible for use with PX5 PAPR systems. Respiratory characteristics are specified on

page 2 of this certificate.

**Technical Specification** and Classifications:

EN 12941:2023 – Respiratory protective devices. Powered filtering devices incorporating a loose fitting respiratory interface. Requirements, testing, marking.

| FILTER   | MMDF      | MIN RUN TIME                               |
|----------|-----------|--|
| HEPA     | 170 l/min | 10.00 hrs (Speed 1)                        |
|          |           | 07.00 hrs (Speed 2)                        |
|          |           | 06.00 hrs (Speed 3)                        |
| Combined | 170 l/min | 05.00 hrs (Speed 1)                        |
|          |           | 04.00 hrs (Speed 2)<br>04.00 hrs (Speed 3) |

EN 166:2001-Personal eye protection. Optical class1 and Medium Impact.

Classification: 1 B

EN 175:1997 Personal eye-protection - Equipment for eye and face protection during welding and allied processes.

EN 379:2003+A1:2009 Personal eye-protection – Automatic Welding Filters Classification: RPB 16-871 - 3/9-13 RPB 1/1/1/2/379 CE (EN 379:2003+A1:2009)

EN 812:2012 Industrial bump caps.

First Issued: 2020-06-02 Effective Date: 2025-07-08 Latest Issue: 2025-07-08 Expiry Date: 2030-06-02

Page: 8 of 11

This certificate has been issued by and remains the property of BSI Group The Netherlands B.V., John M. Keynesplein 9, 1066 EP Amsterdam, The Netherlands and should be returned immediately upon request. To check its validity telephone +31 20 3460780. An electronic certificate can be authenticated online.

No. CE 718714

**Technical Specification** and Classificationscont'd: **Quiet-Slim Ear-Muff** 

EN 352-1:2020 Hearing protectors. General requirements. Earmuffs

 $SNR_m = 29.8$  $SNR_s = 1.9$ SNR(dB) = 28

H84 = 31 dB $H_{\rm m} = 32.7$  $H_s = 1.6$ M84 = 26 dB $M_{m} = 27.8$  $M_{\rm s} = 2.2$ L84 = 19 dB $L_{m} = 21.3$  $L_{\rm s} = 2.6$ 

First Issued: 2020-06-02 Effective Date: 2025-07-08 Latest Issue: 2025-07-08 Expiry Date: 2030-06-02

Page: 9 of 11

This certificate has been issued by and remains the property of BSI Group The Netherlands B.V., John M. Keynesplein 9, 1066 EP Amsterdam, The Netherlands and should be returned immediately upon request. To check its validity telephone +31 20 3460780. An electronic certificate can be authenticated online.

No. CE 718714

Product name: T200 PAPR Respiratory Helmet with Full Face Visor.

Product variants: Face Seal – TH3

Full Hood - TH3

**Product type:** T200 Respiratory Helmet with Full Face Visor & optional Earmuffs.

The T200 Respiratory Helmet with Full Face Visor is designed to only be used as

part of the PX5 AIR Respiratory systems approved to EN 12941:2023.

The T200 is designed to operate with a flow rate between 180-230 litres per minute and compatible for use with PX5 PAPR systems. Respiratory characteristics are

specified on page 2 of this certificate

**Technical Specification and Classifications:** 

EN 12941:2023 – Respiratory protective devices. Powered filtering devices incorporating a loose fitting respiratory interface. Requirements, testing, marking.

| Filter   | MMDF      | Min Run Time        |
|----------|-----------|---------------------|
| HEPA     | 170 l/min | 10.00 hrs (Speed 1) |
|          |           | 07.00 hrs (Speed 2) |
|          |           | 06.00 hrs (Speed 3) |
| Combined | 170 l/min | 05.00 hrs (Speed 1) |
|          |           | 04.00 hrs (Speed 2) |
|          |           | 04.00 hrs (Speed 3) |

EN 166:2001-Personal eye protection. Optical class 1, Low Impact, Liquid Splash.

Classification: 1 F 3

#### **Quiet-Slim Ear-Muff**

EN 352-1:2020 Hearing protectors. General requirements. Earmuffs

$$SNR_m = 29.8$$
  
 $SNR_s = 1.9$   
 $SNR(dB) = 28$ 

First Issued: 2020-06-02 Effective Date: 2025-07-08
Latest Issue: 2025-07-08 Expiry Date: 2030-06-02

Page: 10 of 11

This certificate has been issued by and remains the property of BSI Group The Netherlands B.V., John M. Keynesplein 9, 1066 EP Amsterdam, The Netherlands and should be returned immediately upon request.

No. CE 718714

#### **Certificate Administration Details**

Technical File Reference: PX5 PAPR, T-LINK, Z-LINK, Z4, & T200

#### **Certificate Administration Record and BSI internal Technical File Review refere**

| Issue date    | Comments   | BSI Review Ref.  |
|---------------|--|------------------|
| April 2020    | First issue – PX5 with T-Link.   | 2797:20:3082038  |
| January 2021  | Update to include the Z-Link, Z4 & T200.   | 2797:21:3264883  |
| June 2021     | Scope update to PAPR system to add Combined filters ABEK1P R SL & ABE1P R SL.  Classification upgrade to TH3 Z-Link (Shoulder Cape)  Scope update to Z4 EN 379:2003+A1:2009 & EN 812:2012.  Scope update to Z-Link EN 166:2001 and EN 397:2012+A1:2012.  Scope update to T-Link EN 166:2001 and addition of EN 812:2012  Addition of EN 166:2001 to the TF200. | 2797:21:3410625  |
| February 2024 | Revision of table on page 3.   | 2797:24:30038797 |
| June 2025     | 5 yr renewal; scope update to EN 12941:2023; change in MMDF to 170 l/m; merge scope and contents of CE 698662 Mod B.   | 2797:25:30312560 |

#### **Certificate validity**

The Certificate holder is responsible for ensuring that the Notified Body is advised of changes to any aspect of the overall process utilised in the manufacture of the product, failure to do so could invalidate the Certificate in respect of product manufactured following the introduction of such changes.

#### **Maintenance & Monitoring of manufactured PPE**

The Module B certification requires the continual maintenance and monitoring of the EU conformity to type based on Quality Assurance of the Production Process, Annex VIII (Module D), for the product that are referenced in BSI issued Module D Certificate Number CE 705839.

Page: 11 of 11

This certificate has been issued by and remains the property of BSI Group The Netherlands B.V., John M. Keynesplein 9, 1066 EP Amsterdam, The Netherlands and should be returned immediately upon request.