

PRODUCT SPECIFICATION

Product PN

FI111CAKUN040A00

Mod. 984 c

Rev. 03

Description

Tubular Filter with NY frame and NY mesh 40 um

Tubular filter PA 6,6 frame + 40 um PA mesh



PRODUCT DESCRIPTION	Non-sterile tubular filter with mesh Ny 40µm Product provided in bulk packs for further manufacturing
INTENDED USE / APPLICATION	Transfusion
MATERIALS	Mesh: Polyamide 40 um Housing: Polyamide 6,6 Regulatory Documentation Required: □ Biocompatibility according USP VI □ Rohs, directive 2002/95/CE □ BSE/TSE, directive 2003/32/CE □ DEHP plasticizer Free and latex free □ Reach 1907/2006/CE (hazardous substances regulation) □ Conflict minerals
PRODUCT SHELF LIFE	5 years
STERILIZATION	STERILE:
PACKAGING AND LABELLING	5.000 pcs packed in two PE bags. Bags are separately closed. The first bar-code label is between the 2 bags. The second bar-code label is stuck outside the box. Each bag is labeled with the following traceability information: - Quantity - Product description - Product date - Lot number (OL and batch number to trace back to raw materials used) - Operator code Different lot of goods in one shipment are packed in a manner to prevent mix-ups. Different lots in one box are separately closed and separately labeled to prevent mix-ups.



PRODUCT SPECIFICATION

roduct PN	FI1	11C	AKUN040A00		Mod. 9
escription ^T	ubula	r Filter	with NY frame and NY mesh 40 um		Rev. 0
CERTIFICATE OF COMPLIANCE			y declaration is printed on every invoice and Certificate is according management system in compliance with ISO 9001.	ng to UNI	EN 10204 type 2.1
ACCEPTABLE QUALITY LEVEL	AQ	L (see	table below)		
VISUAL REQUIREMENTS	Inst	trument	t inspection with naked eye and light source of 300-450 mm. Timings: 5 sec per unit		
			Acceptance Requirement	AQL	Sampling Plan
		1	 Plastic support not complete. Loose filter tissue. Short filter mesh, detached from the plastic support. Broken filter mesh. Open mesh out of specification (uneven mesh). *Air bubbles on calotte > 3 mm² 	0.1	
		2	7. Mesh jutting out of the rib. 8. Weld of filter tube out of the rib. 9. Burrs > 0,3 mm. 10. Jutting injection gate >0.3 mm. 11. *Loose particulate matter > 0,1 mm² 12. Plastic material on the filter mesh > 0,5 mm 13. Dents/Scratches with plastic residual	0.65	ISO 2859 part. 1 1st General Inspection Levels
		3	 14. Not detachable filter mesh threads. 15. Dirty of oil, grease. 16. *Embedded particulate matter > 0,2 mm² 	1.5	-



PRODUCT SPECIFICATION

Product PN FI111CAKUN040A00

Mod. 984 c

Description Tubular Filter with NY frame and NY mesh 40 um

DIMENSIONAL REQUIREMENTS

Acceptance Requ	irement	AQL	Sampling Plan
External diameter	15.7 +0.05 -0.10 mm		ISO 2859 part. 1
Base height	3.5 + 0 -0.1 mm	0,1	S3 Special
Internal diameter	11.95 ± 0.2 mm		Inspection Levels

This material specification describes the properties of product above indicated.
This document contains general requirements, material description, drawing references, defect specification, biological material requirements.

REVISIONS AND APPROVALS:

DATE	REV.	REASON FOR CHANGE	ISSUED AND CONTROLLED BY: (name /function and signature)	APPROVED BY: (name /function and signature)
07/05/2019	00	Validation of GVS Microfiltration	P. Carati (PM)	Sara Zaccheroni (AQ) Sava Zacoleuri

Customer Approval:

We accept this n	naterial specification as a part of t	he agreed terms of delivery	
Company name			
Approved by:	(Name, Function)	(Signature)	-
Date		(Company stamp)	

Please send back this document signed for approval. If we will not receive this specification signed, we consider the first order placed as implicit approval.