



Product PN	GIS001A01S GIS001B01S GIS001C01S GIS001D01S GIS002A01S GIS002B01S GIS002C01S GIS002D01S	Mod. 984e-ext Rev. 07
Description	HI-FLO IV Set Adult 0.2/1.2 µm Easydrop/Eurodrop® single/double scale	

HI-FLO IV Set Adult with 0.2/1.2 µm Filter, Regulator and Roller

PRODUCT DESCRIPTION	<p>Infusion set infusion for intravascular applications.</p> <p>The device is sterile and is for gravity feed infusion only.</p> <p>The set has a vented IV drip chamber (20 drops/ml) and a male luer lock outlet with ring and protective cap, compliant with ISO 80369-7.</p> <p>The set is provided with a vented Speedflow® Adult filter, with an hydrophilic PES membrane with 0.2/1.2 µm pore size for particles retention and a hydrophobic PTFE membrane with 0,03 µm pore size.</p> <p>The set also includes a roller and a flow regulator Easydrop/Eurodrop® single/double scale, to approximately regulate the flow rate.</p> <p>The set is provided with a y-injection site, for administration of additional drugs by means of a syringe using the same infusion line, and with a clamp.</p> <p>The approximate total length of the set is 2171 mm.</p> <p>The set includes the following components:</p> <ul style="list-style-type: none">▪ Drip Chamber (20 drops/ml);▪ Roller;▪ Flow regulator Easydrop®/Eurodrop® single/double scale;▪ Y-Injection point;▪ Speedflow® Adult 0.2/1.2 µm IV Filter;▪ Clamp;▪ Male luer lock outlet with ring and protective cap.																
CONFIGURATIONS	<table><tr><td>GIS001A01S</td><td>0.2 µm with Easydrop® single scale</td></tr><tr><td>GIS001B01S</td><td>0.2 µm with Easydrop® double scale</td></tr><tr><td>GIS001C01S</td><td>0.2 µm with Eurodrop® single scale</td></tr><tr><td>GIS001D01S</td><td>0.2 µm with Eurodrop® double scale</td></tr><tr><td>GIS002A01S</td><td>1.2 µm with Easydrop® single scale</td></tr><tr><td>GIS002B01S</td><td>1.2 µm with Easydrop® double scale</td></tr><tr><td>GIS002C01S</td><td>1.2 µm with Eurodrop® single scale</td></tr><tr><td>GIS002D01S</td><td>1.2 µm with Eurodrop® double scale</td></tr></table>	GIS001A01S	0.2 µm with Easydrop® single scale	GIS001B01S	0.2 µm with Easydrop® double scale	GIS001C01S	0.2 µm with Eurodrop® single scale	GIS001D01S	0.2 µm with Eurodrop® double scale	GIS002A01S	1.2 µm with Easydrop® single scale	GIS002B01S	1.2 µm with Easydrop® double scale	GIS002C01S	1.2 µm with Eurodrop® single scale	GIS002D01S	1.2 µm with Eurodrop® double scale
GIS001A01S	0.2 µm with Easydrop® single scale																
GIS001B01S	0.2 µm with Easydrop® double scale																
GIS001C01S	0.2 µm with Eurodrop® single scale																
GIS001D01S	0.2 µm with Eurodrop® double scale																
GIS002A01S	1.2 µm with Easydrop® single scale																
GIS002B01S	1.2 µm with Easydrop® double scale																
GIS002C01S	1.2 µm with Eurodrop® single scale																
GIS002D01S	1.2 µm with Eurodrop® double scale																
MANUFACTURER NAME	<p>GVS S.p.A.</p> <p>Via Roma, 50 – 40069 Zola Predosa (BO) – Italy</p> <p>Phone : +39.051.6176311 – Fax: +39.051.6176200</p> <p>email: gvs@gvs.it – website: www.gvs.com</p>																
INTENDED USE / APPLICATION	<p>Infusion of Drugs (including chemotherapy), Anesthetics, Nutritional Solutions and Saline Solutions for intravascular applications.</p> <p>The set can be connected via Luer Locks to all commercially available infusion administration sets compliant with ISO 80369-7.</p> <p>The set is for gravity feed infusion.</p> <p>The set with 0.2 µm filter is intended specifically to eliminate air bubbles and to retain particles and bacteria, while the set with 1.2 µm filter is intended specifically to eliminate air bubbles and to retain fungi and microorganisms.</p> <p>The set is a single-use device that can be used applications that last:</p> <ul style="list-style-type: none">▪ Devices with 0.2 µm filter: up to 96 hours;▪ Devices with 1.2 µm filter: up to 24 hours. <p>The set has to be disposed after each therapy.</p> <p>Sets with 0.2 µm filter cannot be used for infusion of hyper alimentation liquids, lipids, blood and/or blood derivatives.</p> <p>Sets with 1.2 µm filter cannot be used for infusion of blood and/or blood derivatives.</p> <p>The device should only be supervised and used by qualified healthcare personnel.</p>																
CLASS OF THE PRODUCT	<p>Class IIa – sterile – single use</p> <p>Rule 2 and 3 Annex VIII 2017/745/UE</p>																



PRODUCT SPECIFICATION

CE 0051

Product PN	GIS001A01S GIS001B01S GIS001C01S GIS001D01S GIS002A01S GIS002B01S GIS002C01S GIS002D01S	Mod. 984e-ext Rev. 07
Description	HI-FLO IV Set Adult 0.2/1.2 µm Easydrop/Eurodrop® single/double scale	

REGISTRATION NUMBERS	Italian national database: GIS001A01S 2439274 GIS001B01S 2439280 GIS001C01S 2439284 GIS001D01S 2439288 GIS002A01S 2439275 GIS002B01S 2439281 GIS002C01S 2439285 GIS002D01S 2439289	
EMDN	A03010102 INFUSION CONTROLLERS WITH FILTER (ALSO TRANSFUSION CONTROLLERS)	
MATERIALS	Filter media: PES Hydrophilic membrane / PTFE Hydrophobic membrane Filter housing: MBS Tubes: PVC (DEHP Free) Flow Regulator: SEBS / ABS / Alkyl Polysiloxane Roller: HDPE Drip Chamber: ABS / PVC (DEHP Free) / LDPE / HDPE / PA6.6 / NY Y-injection: SEBS / MABS Clamp: PP / LDPE Luer Lock: MABS Cap: HDPE / PE Regulatory Compliance: <ul style="list-style-type: none">▪ Biocompatibility according to ISO 10993-1▪ Rohs, directive 2011/65/EU▪ DEHP plasticizer Free▪ Latex free▪ Reach 1907/2006/CE (hazardous substances regulation)▪ Reg. 1272/2008/CE (classification, labelling and packaging of substances and mixtures)	
PRODUCT CHARACTERISTICS	Physical/Mechanical: Approximate total length: 2171 mm Total internal volume of the set: 32.0 ml Weight (approx.): 47 g Input/output connectors: Male luer lock outlet with ring and protective cap compliant with ISO 80369-7 Operating temperature Range: From 5 °C to 40 °C Storage temperature Range: From 0 °C to 40 °C Biological: Biocompatibility: Compliant with ISO 10993-1 Features: Type of administration: gravity Duration of the application: 0.2 µm up to 96 hours 1.2 µm up to 24 hours Speedflow Adult 0.2/1.2 µm vented Filter: Speedflow Adult 0.2/1.2 µm vented Filter pore size: 0.2/1.2 µm Filter internal volume: < 2.4 ml Filter media: hydrophilic PES membrane and hydrophobic PTFE membrane Flow Regulator: Easydrop®/Eurodrop® single/double scale Drip Chamber: Yes – 20 drops / ml Roller: Yes Y-injection site: Yes Clamp: Yes Tubing: PVC tube – inner Ø 3.0 mm / outer Ø 4.1 mm	
PRODUCT SHELF LIFE	5 years	
STERILIZATION	Sterile: Yes – EtO Suitable for Sterilization/Re-sterilization: No	



PRODUCT SPECIFICATION




Product PN	GIS001A01S GIS001B01S GIS001C01S GIS001D01S GIS002A01S GIS002B01S GIS002C01S GIS002D01S	Mod. 984e-ext Rev. 07
Description	HI-FLO IV Set Adult 0.2/1.2 µm Easydrop/Eurodrop® single/double scale	

APPLICABLE STANDARDS AND REGULATIONS	Product Certification:	CE mark
	Applicable Standards and Technical Regulations:	
	EN 556-1	Sterilization of medical devices — Requirements for medical devices to be designated "STERILE" — Part 1: Requirements for terminally sterilized medical devices
	EN ISO 8536-4	Infusion equipment for medical use — Part 4: Infusion sets for single use, gravity feed
	EN ISO 8536-11	Infusion equipment for medical use — Part 11: Infusion filters for single use with pressure infusion equipment
	EN ISO 8536-13	Infusion equipment for medical use — Part 13: Graduated flow regulators for single use with fluid contact
	EN ISO 8536-14	Infusion equipment for medical use — Part 14: Clamps and flow regulators for transfusion and infusion equipment without fluid contact
	EN ISO 10993-1	Biological evaluation of medical devices — Part 1: Evaluation and testing within a risk management process
	EN ISO 10993-4	Biological evaluation of medical devices — Part 4: Selection of tests for interactions with blood
	EN ISO 10993-5	Biological evaluation of medical devices — Part 5: Tests for in vitro cytotoxicity
	EN ISO 10993-7	Biological evaluation of medical devices — Part 7: Ethylene oxide sterilization residuals
	EN ISO 10993-10	Biological evaluation of medical devices — Part 10: Tests for irritation and skin sensitization
	EN ISO 10993-11	Biological evaluation of medical devices — Part 11: Tests for systemic toxicity
	EN ISO 10993-18	Biological evaluation of medical devices — Part 18: Chemical characterization of materials
	EN ISO 10993-23	Biological evaluation of medical devices — Part 23: Tests for irritation
	EN ISO 11135	Sterilization of health-care products — Ethylene oxide — Requirements for the development, validation and routine control of a sterilization process for medical devices
	EN ISO 11607-1	Packaging for terminally sterilized medical devices — Part 1: Requirements for materials, sterile barrier systems and packaging systems
	EN ISO 11607-2	Packaging for terminally sterilized medical devices — Part 2: Validation requirements for forming, sealing and assembly processes
	EN ISO 13485	Medical devices — Quality management systems — Requirements for regulatory purposes
	EN ISO 14971	Medical devices — Application of risk management to medical devices
	EN ISO 15223-1	Medical devices — Symbols to be used with medical device labels, labelling and information to be supplied — Part 1: General requirements
	EN ISO 20417	Medical devices — Information to be supplied by the manufacturer
	IEC 62366-1	Medical devices — Part 1: Application of usability engineering to medical devices
	EN ISO 80369-1	Small-bore connectors for liquids and gases in healthcare applications — Part 1: General requirements
	EN ISO 80369-7	Small-bore connectors for liquids and gases in healthcare applications — Part 7: Connectors for intravascular or hypodermic applications
	EN ISO 80369-20	Small-bore connectors for liquids and gases in healthcare applications — Part 20: Common test methods
INSTRUCTIONS FOR USE	Available languages:	English / Italian / German / French / Spanish / Hungarian / Romanian
PACKAGING	Primary Packaging:	Devices are individually packed and label in medical paper bags. Bag Size: 150 X 250 mm
	Secondary Packaging:	Bags are placed inside a microperforated sack.
	Tertiary Packaging:	Carton Box. Box Size: 60 x 40 x 20 cm Box Weight: 4.5 kg Devices per box: 70
CERTIFICATIONS	ISO 9001:2015 ISO 13485:2016 CE Certificate (2017/745/UE)	



Product PN	GIS001A01S GIS001B01S GIS001C01S GIS001D01S GIS002A01S GIS002B01S GIS002C01S GIS002D01S	Mod. 984e-ext Rev. 07
Description	HI-FLO IV Set Adult 0.2/1.2 µm Easydrop/Eurodrop® single/double scale	

DRAWING



ID	Description
1	Drip Chamber 20 drops/ml
2	Tube 75 cm – inner Ø 3.0 mm / outer Ø 4.1 mm
3	Roller
4	'A' model: Flow Regulator Easydrop® single scale 'B' model: Flow Regulator Easydrop® double scale 'C' model: Flow Regulator Eurodrop® single scale 'D' model: Flow Regulator Eurodrop® double scale
5	Y-Injection site
6	'1' model: Speedflow Adult 0.2 µm IV filter '2' model: Speedflow Adult 1.2 µm IV filter
7	Clamp
8	Tube 15 cm – inner Ø 3.0 mm / outer Ø 4.1 mm
9	Male Luer Lock with ring and protective cap

REVISIONS AND APPROVALS:

DATE	REV.	REASON FOR CHANGE	ISSUED BY: (name/function/signature)	VERIFIED BY: (name/function/signature)	APPROVED BY: (name/function/signature)
14/02/2025	02	Added Hungarian and Romanian translations on labels and IFU	Barbara Palmieri RA Specialist 	Barbara Finessi QA Manage 	Luca Zanini VP Healthcare and Lifesience 